



Results for "((linear sampling<in>ab) <or> (exponential sampling<in>ab) <or> (natural log sampling<in>ab)) <and> (pyr >= 1950 <and> pyr <= 2000)"  

Your search matched 24 of 1166705 documents. You selected 19 items.

Display Format: ☐ Citation ☒ Citation & Abstract

Article Information

[View: 1-19](#) | [View Search](#)

Download Citations

Choose

Citation

Download

EndNote, ProCite, RefMan

Download

[» Learn more](#)

» Key

IEEE JNL IEEE Journal or Magazine

IEE JNL IEE Journal or Magazine

IEEE CNF IEEE Conference Proceeding

IEE CNF IEE Conference Proceeding

IEEE STD IEEE Standard

1. **Stability analysis of a CSI-fed Inductor motor with digital vector controller**
Tsuji, M.; Yamada, E.; Izumi, K.; Oyama, J.
Power Electronics Specialists Conference, 1988. PESC '88 Record., 19th Annual IEEE
11-14 Apr 1988
Page(s): 885-892 vol.2
Summary: A linear sampled-data model for a current source inverter (CSI)-fed induction-motor vector control system which is controlled digitally by a microprocessor is derived. The system stability is discussed from viewpoints of sampling period, micropro.....
[AbstractPlus](#) | Full Text: [PDF](#) [IEEE CNF](#)
2. **A sampled-data control scheme for stabilization of systems with unmodeled high-frequency dynamics**
Barbot, J.P.; Pantalos, N.
Automatic Control, IEEE Transactions on
Volume: 37 Issue: 2 Feb 1992
Page(s): 285-288
Summary: The output feedback stabilization problem is considered for linear sampled-data control systems in the presence of unmodeled high-frequency dynamics. Sufficient conditions for stabilization of such systems are given by M. Vidyasagar (1985) for strictly positive real systems.....
[AbstractPlus](#) | Full Text: [PDF](#) [IEEE JNL](#)
3. **Simple frequency estimation via exponential samples**
Kay, S.
Signal Processing Letters, IEEE
Volume: 1 Issue: 5 May 1994
Page(s): 73-75
Summary: A method for determining the frequency of a real sinusoid is proposed. Based on exponential sampling of the waveform, the approach requires virtually no computation. It can be easily implemented in hardware.....
[AbstractPlus](#) | Full Text: [PDF](#) [IEEE JNL](#)
4. **Output feedback control of sampled-data systems with parametric uncertainties**
Shi, P.; Xie, L.; de Souza, C.E.
Decision and Control, 1992., Proceedings of the 31st IEEE Conference on
1992
Page(s): 2876-2881 vol.3
Summary: The design of robust control for linear sampled-data systems with parametric uncertainty is considered. Emphasis is placed on linear dynamic output feedback controllers, and two problems are addressed. The first is robust stabilization while the second is robust tracking.....
[AbstractPlus](#) | Full Text: [PDF](#) [IEEE CNF](#)
5. **Resolution analysis in signal recovery**
Dharanipragada, S.; Arun, K.S.
Acoustics, Speech, and Signal Processing, 1995. ICASSP-95., 1995 International Conference on
Volume: 2 9-12 May 1995
Page(s): 889-892 vol.2
Summary: Resolution analysis for the problem of signal recovery from finitely many linear samples is the subject of the paper. The classical Rayleigh limit serves only as a lower bound on resolution since it does not assume any recovery strategy and is based on the Rayleigh limit.....
[AbstractPlus](#) | Full Text: [PDF](#) [IEEE CNF](#)
6. **Region-of-interest tomography using the wavelet transform and angular harmonics**
Yagle, A.E.

Image Processing, 1995. Proceedings., International Conference on

Volume: 2 23-26 Oct 1995

Page(s): 461-463 vol.2

Summary: Some authors have shown that wavelets can be used to localize the Radon transform, i.e., to reconstruct a small region of interest (ROI) from projections densely sampled in the ROI and sparsely sampled outside it. A different approach using Fourier e.....

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE CNF](#)

7. Some issues on disturbance rejection for linear sampled data control systems

Xie, J.Q.; Farooq, M.

Industrial Electronics Society, 1998. IECON '98. Proceedings of the 24th Annual Conference of the IEEE

Volume: 3 31 Aug-4 Sep 1998

Page(s): 1499-1504 vol.3

Summary: In the design of linear sampled data control systems, tradeoffs between achievable performance and disturbance rejection (sensitivity reduction) always manifest themselves. However, when disturbance rejection is considered to be the first priority, t.....

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE CNF](#)

8. On the exact recovery of cumulants

Cheded, L.

Signal Processing Proceedings, 1998. ICSP '98. 1998 Fourth International Conference on
1998

Page(s): 423-426 vol.1

Summary: The importance of higher-order statistics (HOS) is clearly reflected in their increasingly wide applicability. However, because of the high dimensionality involved, the digital estimation of HOS is still plagued by heavy computational loads which tend to.....

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE CNF](#)

9. Non-linear time scale transformation for the analysis of multiexponential decays

Palacin, J.; Marco, S.; Samitier, J.

Instrumentation and Measurement Technology Conference, 1999. IMTC/99. Proceedings of the 16th IEEE

Volume: 2 1999

Page(s): 1178-1182 vol.2

Summary: Multiexponential decays may contain time-constants differing in several orders of magnitudes. In such cases linear sampling results in very long records featuring a high degree of oversampling. Here, we analyze a nonlinear linear time scale transformation.....

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE CNF](#)

10. Wavelet design of time-varying filters

Ridsdill-Smith, T.A.

Signal Processing and Its Applications, 1999. ISSPA '99. Proceedings of the Fifth International Symposium

Volume: 2 1999

Page(s): 599-602 vol.2

Summary: Linear time-varying filters can be efficiently implemented using a construction based on the wavelet transform. The method generates a vector of weights for the wavelet coefficients, known as the scale filter coefficients, using least-squares techniques.....

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE CNF](#)

11. Parameter estimation of geometrically sampled fractional Brownian traffic

Vidacs, A.; Virtamo, J.T.

INFOCOM 2000. Nineteenth Annual Joint Conference of the IEEE Computer and Communications Society
Proceedings. IEEE

Volume: 3 26-30 Mar 2000

Page(s): 1791-1796 vol.3

Summary: The parameter estimation of a traffic model based on the fractional Brownian motion (FBM) is studied. The model has three parameters: the mean rate m , variance parameter a and the Hurst parameter H . Explicit expressions for the maximum likelihood (ML).....

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE CNF](#)

12. Fast Hankel transform by fast sine and cosine transforms: the Mellin connection

Knockaert, L.

Signal Processing, IEEE Transactions on [see also Acoustics, Speech, and Signal Processing, IEEE Transactions on]

Volume: 48 Issue: 6 Jun 2000

Page(s): 1695-1701

Summary: The Hankel transform of a function by means of a direct Mellin approach requires sampling on an exponential grid, which has the disadvantage of coarsely undersampling the tail of the function. A novel fast Hankel transform procedure that does not.....

13. Physical Realization of the Impedance Function of Short-Circuited Cascade of Uniform Lossless Transmission Lines (SCULL)

Jury, E.

Circuits and Systems, IEEE Transactions on [legacy, pre - 1988]

Volume: 19 Issue: 1 Jan 1972

Page(s): 100- 103

Summary: In this correspondence the relationship between type-L₁ stability criterion for uniformly sampled and distributed parameter systems and the table form of stability of linear sampled-data systems is shown. A simple necessary condition is given.

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE JNL](#)

14. On the stability of pulse-width-modulated feedback systems

Skoog, R.

Automatic Control, IEEE Transactions on

Volume: 13 Issue: 5 Oct 1968

Page(s): 532- 538

Summary: The objective of this paper is to present a frequency-domain stability criterion for pulse-width modulated feedback systems. The criterion states that 1) if the Nyquist locus of the pulse transfer function of the linear plant does not intersect or encircle the point -1, the system is stable.

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE JNL](#)

15. An extended frequency-domain stability criterion for a class of sampled-data systems

Shortle, G., Jr.; Alexandro, F., Jr.

Automatic Control, IEEE Transactions on

Volume: 15 Issue: 2 Apr 1970

Page(s): 232- 234

Summary: A new frequency-domain stability criterion employing a Popov-type multiplier is obtained for a class of nonlinear sampled-data control systems containing a monotonically nondecreasing nonlinearity. This criterion is an extension of previous results.

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE JNL](#)

16. On sampled-data optimization in distributed parameter systems

Lee, K.; Barr, R.

Automatic Control, IEEE Transactions on

Volume: 17 Issue: 6 Dec 1972

Page(s): 806- 809

Summary: A system of parabolic partial differential equations is transformed into ordinary differential equations in a Hilbert space, where the system operator is the infinitesimal generator of a semigroup of operators. The sampled-data problem is then formulated.

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE JNL](#)

17. Statistical evaluation of digital-analog systems for finite operating time

Northrop, R.; Johnson, G.

Automatic Control, IRE Transactions on

Volume: 5 Issue: 2 Jun 1960

Page(s): 118- 128

Summary: A frequency-domain mathematical model for comparing the performance of a linear sampled-data channel to a linear continuous channel is developed. The model assumes a suddenly applied stationary random input (input identically zero before the local time t_0).

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE JNL](#)

18. An extreme value problem in a linear sampled-data feedback system

Knowles, J.

Automatic Control, IEEE Transactions on

Volume: 8 Issue: 3 Jul 1963

Page(s): 235- 239

Summary: When an uncorrelated, wide-band Markov noise process contaminates the input signal to a linear sampled-data feedback system, the extreme values of the mean-square true error and the mean-square apparent error are shown to occur for most practical purposes.

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE JNL](#)

19. Synthesis of linear antenna arrays using Z transforms

Gaushell, D.

Antennas and Propagation, IEEE Transactions on [legacy, pre - 1988]

Volume: 19 Issue: 1 Jan 1971

Page(s): 75- 80



Summary: It is well known that a linear antenna array with equally spaced elements can be represented polynomial whose roots correspond to the nulls of its antenna pattern. Since the linear array has equally spaced elements, its polynomial has only integer roots.

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE JNL](#)

[View: 1-19](#) | [View Search Results](#) | [Back](#)

[Help](#) [Contact Us](#) [Privacy & Security](#)

© Copyright 2005 IEEE – All Rights Reserved

Results for "((linear sampling<in>ab) <or> (exponential sampling<in>ab) <or> (natural log sampling<in>ab)) <and> (pyr >= 1950 <and> pyr <= 2000)"  

Your search matched 24 of 1166705 documents. You selected 19 items.

Display Format: ☐ Citation ☒ Citation & Abstract

Article Information

[View: 1-19](#) | [View Search](#)

Download Citations

Choose

Citation

Download

EndNote, ProCite, RefMan

Download

[» Learn more](#)

» Key

IEEE JNL IEEE Journal or Magazine

IEEE JNL IEEE Journal or Magazine

IEEE CNF IEEE Conference Proceeding

IEEE CNF IEEE Conference Proceeding

IEEE STD IEEE Standard

1. Stability analysis of a CSI-fed inductor motor with digital vector controller

Tsuji, M.; Yamada, E.; Izumi, K.; Oyama, J.

Power Electronics Specialists Conference, 1988. PESC '88 Record., 19th Annual IEEE

11-14 Apr 1988

Page(s): 885-892 vol.2

Summary: A linear sampled-data model for a current source inverter (CSI)-fed induction-motor vector control system which is controlled digitally by a microprocessor is derived. The system stability is discussed from viewpoints of sampling period, micropro.....

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE CNF](#)

2. A sampled-data control scheme for stabilization of systems with unmodeled high-frequency dynamics

Barbot, J.P.; Pantalos, N.

Automatic Control, IEEE Transactions on

Volume: 37 Issue: 2 Feb 1992

Page(s): 285-288

Summary: The output feedback stabilization problem is considered for linear sampled-data control systems in the presence of unmodeled high-frequency dynamics. Sufficient conditions for stabilization of such systems are given by M. Vidyasagar (1985) for strictly positive real systems.....

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE JNL](#)

3. Simple frequency estimation via exponential samples

Kay, S.

Signal Processing Letters, IEEE

Volume: 1 Issue: 5 May 1994

Page(s): 73-75

Summary: A method for determining the frequency of a real sinusoid is proposed. Based on exponential sampling of the waveform, the approach requires virtually no computation. It can be easily implemented in hardware.....

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE JNL](#)

4. Output feedback control of sampled-data systems with parametric uncertainties

Shi, P.; Xie, L.; de Souza, C.E.

Decision and Control, 1992., Proceedings of the 31st IEEE Conference on

1992

Page(s): 2876-2881 vol.3

Summary: The design of robust control for linear sampled-data systems with parametric uncertainty is considered. Emphasis is placed on linear dynamic output feedback controllers, and two problems are addressed. The first is robust stabilization while the second is robust tracking.....

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE CNF](#)

5. Resolution analysis in signal recovery

Dharanipragada, S.; Arun, K.S.

Acoustics, Speech, and Signal Processing, 1995. ICASSP-95., 1995 International Conference on

Volume: 2 9-12 May 1995

Page(s): 889-892 vol.2

Summary: Resolution analysis for the problem of signal recovery from finitely many linear samples is the subject of the paper. The classical Rayleigh limit serves only as a lower bound on resolution since it does not assume any recovery strategy and is based on.....

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE CNF](#)

6.

Region-of-interest tomography using the wavelet transform and angular harmonics

Yagle, A.E.

Image Processing, 1995. Proceedings, International Conference on
Volume: 2 23-26 Oct 1995
Page(s): 461-463 vol.2

Summary: Some authors have shown that wavelets can be used to localize the Radon transform, i.e., to reconstruct a small region of interest (ROI) from projections densely sampled in the ROI and sparsely sampled outside it. A different approach using Fourier e.....

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE CNF](#)

7. Some issues on disturbance rejection for linear sampled data control systems

Xie, J.Q.; Farooq, M.

Industrial Electronics Society, 1998. IECON '98. Proceedings of the 24th Annual Conference of the IEEE
Volume: 3 31 Aug-4 Sep 1998

Page(s): 1499-1504 vol.3

Summary: In the design of linear sampled data control systems, tradeoffs between achievable performance and disturbance rejection (sensitivity reduction) always manifest themselves. However, when disturbance rejection is considered to be the first priority, t.....

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE CNF](#)

8. On the exact recovery of cumulants

Cheded, L.

Signal Processing Proceedings, 1998. ICSP '98. 1998 Fourth International Conference on
1998

Page(s): 423-426 vol.1

Summary: The importance of higher-order statistics (HOS) is clearly reflected in their increasingly wide applicability. However, because of the high dimensionality involved, the digital estimation of HOS is still plagued by heavy computational loads which tend to.....

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE CNF](#)

9. Non-linear time scale transformation for the analysis of multiexponential decays

Palacin, J.; Marco, S.; Samitier, J.

Instrumentation and Measurement Technology Conference, 1999. IMTC/99. Proceedings of the 16th IEEE
Volume: 2 1999

Page(s): 1178-1182 vol.2

Summary: Multiexponential decays may contain time-constants differing in several orders of magnitudes. In such cases linear sampling results in very long records featuring a high degree of oversampling. Here, we analyze a nonlinear linear time scale transformation.....

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE CNF](#)

10. Wavelet design of time-varying filters

Ridsdill-Smith, T.A.

Signal Processing and Its Applications, 1999. ISSPA '99. Proceedings of the Fifth International Symposium
Volume: 2 1999

Page(s): 599-602 vol.2

Summary: Linear time-varying filters can be efficiently implemented using a construction based on the wavelet transform. The method generates a vector of weights for the wavelet coefficients, known as the scale filter coefficients, using least-squares techniques.....

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE CNF](#)

11. Parameter estimation of geometrically sampled fractional Brownian traffic

Vidacs, A.; Virtamo, J.T.

INFOCOM 2000. Nineteenth Annual Joint Conference of the IEEE Computer and Communications Society
Proceedings. IEEE

Volume: 3 26-30 Mar 2000

Page(s): 1791-1796 vol.3

Summary: The parameter estimation of a traffic model based on the fractional Brownian motion (FBM) is studied. The model has three parameters: the mean rate m , variance parameter a and the Hurst parameter H . Explicit expressions for the maximum likelihood (ML) estimates are derived.....

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE CNF](#)

12. Fast Hankel transform by fast sine and cosine transforms: the Mellin connection

Knockaert, L.

Signal Processing, IEEE Transactions on [see also Acoustics, Speech, and Signal Processing, IEEE Transactions on]

Volume: 48 Issue: 6 Jun 2000

Page(s): 1695-1701

Summary: The Hankel transform of a function by means of a direct Mellin approach requires sampling on an exponential grid, which has the disadvantage of coarsely undersampling the tail of the function. A novel fast Hankel transform procedure that does not.....

- 13. Physical Realization of the Impedance Function of Short-Circuited Cascade of Uniform Lossless Transmission Lines (SCULL)**
Jury, E.
Circuits and Systems, IEEE Transactions on [legacy, pre - 1988]
Volume: 19 Issue: 1 Jan 1972
Page(s): 100- 103
Summary: In this correspondence the relationship between type-L₁ stability criterion for uniformly sampled and distributed parameter systems and the table form of stability of linear sampled-data systems is shown. A simple necessary condition is derived.....
[AbstractPlus](#) | Full Text: [PDF](#) [IEEE JNL](#)
- 14. On the stability of pulse-width-modulated feedback systems**
Skoog, R.
Automatic Control, IEEE Transactions on
Volume: 13 Issue: 5 Oct 1968
Page(s): 532- 538
Summary: The objective of this paper is to present a frequency-domain stability criterion for pulse-width modulated feedback systems. The criterion states that 1) if the Nyquist locus of the pulse transfer function of the linear plant does not intersect or encircle the point -1 in the complex plane, the system is stable.....
[AbstractPlus](#) | Full Text: [PDF](#) [IEEE JNL](#)
- 15. An extended frequency-domain stability criterion for a class of sampled-data systems**
Shortle, G., Jr.; Alexandro, F., Jr.
Automatic Control, IEEE Transactions on
Volume: 15 Issue: 2 Apr 1970
Page(s): 232- 234
Summary: A new frequency-domain stability criterion employing a Popov-type multiplier is obtained for a class of nonlinear sampled-data control systems containing a monotonically nondecreasing nonlinearity. This criterion is an extension of previous results.....
[AbstractPlus](#) | Full Text: [PDF](#) [IEEE JNL](#)
- 16. On sampled-data optimization in distributed parameter systems**
Lee, K.; Barr, R.
Automatic Control, IEEE Transactions on
Volume: 17 Issue: 6 Dec 1972
Page(s): 806- 809
Summary: A system of parabolic partial differential equations is transformed into ordinary differential equations in a Hilbert space, where the system operator is the infinitesimal generator of a semigroup of operators. A sampled-data problem is then formulated.....
[AbstractPlus](#) | Full Text: [PDF](#) [IEEE JNL](#)
- 17. Statistical evaluation of digital-analog systems for finite operating time**
Northrop, R.; Johnson, G.
Automatic Control, IEEE Transactions on
Volume: 5 Issue: 2 Jun 1960
Page(s): 118- 128
Summary: A frequency-domain mathematical model for comparing the performance of a linear sampled-data channel to a linear continuous channel is developed. The model assumes a suddenly applied stationary random input (input identically zero before the local time.....
[AbstractPlus](#) | Full Text: [PDF](#) [IEEE JNL](#)
- 18. An extreme value problem in a linear sampled-data feedback system**
Knowles, J.
Automatic Control, IEEE Transactions on
Volume: 8 Issue: 3 Jul 1963
Page(s): 235- 239
Summary: When an uncorrelated, wide-band Markov noise process contaminates the input signal to a linear sampled-data feedback system, the extreme values of the mean-square true error and the mean-square apparent error are shown to occur for most practical parameters.....
[AbstractPlus](#) | Full Text: [PDF](#) [IEEE JNL](#)
- 19. Synthesis of linear antenna arrays using Z transforms**
Gaushell, D.
Antennas and Propagation, IEEE Transactions on [legacy, pre - 1988]
Volume: 19 Issue: 1 Jan 1971

Page(s): 75- 80

Summary: It is well known that a linear antenna array with equally spaced elements can be represented polynomial whose roots correspond to the nulls of its antenna pattern. Since the linear array has equally : elements, its polynomial has only inte.....

[AbstractPlus](#) | Full Text: [PDF](#) [IEEE JNL](#)

[View: 1-19](#) | [View Search Results](#) | [Ba](#)

[Help](#) [Contact Us](#) [Privacy & Security](#)

© Copyright 2005 IEEE – All Rights